

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-174175

(43)Date of publication of application : 21.06.2002

(51)Int.Cl. F04B 37/16
 F04B 49/06
 F04C 23/00
 F04C 25/02

(21)Application number : 2000-370714

(71)Applicant : TEIJIN SEIKI CO LTD


(22)Date of filing : 05.12.2000 (72)Inventor : ANDO KIYOSHI

(54) EVACUATOR

(57)Abstract:

PROBLEM TO BE SOLVED: To provide an evacuator high in energy efficiency at the time when pressure on the air intake side is arrival pressure or vacuum to a certain degrees by reducing motive power by differential pressure.

SOLUTION: The multistage type evacuator 100 furnished with a roughing pump B and a booster pump A is constituted to be high in energy efficiency by installing a ceiling pump C on the atmospheric air side of the final stage roughing pump B and making designed exhaust speed of the ceiling pump C in size enough to function as the ceiling pump even though it is lower than designed exhaust speed of the roughing pump B.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]